

<b>Model Code</b>	<b>LT434P-6S-V</b>
<b>Specification</b>	
<b>Dimensions</b>	
Overall Length (mm)	11,010
Overall Width (mm)	2,450
Wheelbase (mm)	5,700
G.V.W. (kg)	14,800
<b>Engine</b>	
Model	6HK1E5NC
Type	OHC, Direct Injection, Turbo Charged with intercooler, EGR, Watercooled, 6 cylinders, Common Rail System, DOC System
Displacement (cc)	7,790
Max. Output	240 ps / 2,400 rpm
Max. Torque	72kg-m / 1,400 ~2,400rpm
<b>Transmission</b>	
Type	MZW6P 6-speed overdrive
Gear ratio	1st ~ 6th: 6.615 ~ 0.722
Final Gear ratio	5.571
<b>Clutch</b>	
Type	Dry single plate w/cushioning spring,
<b>Steering</b>	
Type	Recirculating ball, power assisted
<b>Suspension</b>	
Front & Rear	Air suspension with stabilizer
<b>Brake</b>	
Service	Full air, Dual Circuit, ABS and air dryer, Brake auto adjuster
Parking	Spring brake actuators acting on rear wheels
Auxiliary	Permanent magnetic retarder(option), Exhaust Brake
<b>Tire &amp; Disc</b>	
Disc Wheel	22.5 X 8.25 (10 studs)
Tire	11R22.5-14PR Radial Tubeless
<b>Standard Equipment</b>	
	Clutch minipack control, Exhaust brake, Air dryer, Anti Lock brake system, Spare tire with carrier, Tachometer, Abestos free brake & clutch linings

<b>型號</b>	<b>LT434P-6S-V</b>
<b>規格</b>	
<b>車陣尺寸</b>	
全長(毫米)	11,010
全闊(毫米)	2,450
軸距(毫米)	5,700
總重量 (公斤)	14,800
<b>引擎</b>	
型號	6HK1E5NC
類別	頂置凸輪軸，直接噴注，渦輪增壓附中置冷卻器，廢氣再循環裝置，水冷式，6 氣缸，電子控制高壓共軌噴注系統，DOC 系統
汽缸容積 (cc)	7,790
最大輸出	240 ps / 2,400 rpm
最大扭力	72kg-m / 1,400 ~2,400rpm
<b>波箱</b>	
型號	MZW6P 6前速超速檔
波段比	1波 ~ 6 波: 6.615 ~ 0.722
最終傳動比	5.571
<b>離合器</b>	
類別	單乾板式附緩衝彈簧，液壓控制
<b>轉向系統</b>	
類別	迴旋走珠式，動力輔助
<b>懸掛系統</b>	
類別	氣壓懸掛附吸震筒
<b>制動系統</b>	
制動操作	全風雙迴路，防鎖剎車系統 (ABS)，自動攝迫力皮
泊車手制	後輪彈簧制動器
輔助制動系統	恆久式磁力輔助制動器(附加設備)，廢氣制動
<b>車胎</b>	
車輪	22.5 X 8.25 (10螺絲)
輪胎	11R22.5-14PR 無內膽原子胎
<b>標準裝備</b>	
	動力輔助離合器，廢氣制動，空氣乾燥器，防鎖剎車系統 (ABS)，後備輪軸連架，引擎轉數錶，無石棉環保迫力皮及離合器片

042014

- 以上規格如有更改，恕不另行通告。  
- 圖示之設備可能與實物稍異。  
- 備有耗油量資料可供查閱。  
此引擎符合廢氣管制環保5(Euro5)  
及香港噪音管制標準。

<b>Model Code</b>	<b>LV434V</b>
<b>Specification</b>	
<b>Dimensions</b>	
Overall Length (mm)	8,654
Overall Width (mm)	2,447
Wheelbase (mm)	3,000
G.V.W. (kg)	16,000
<b>Engine</b>	
Model	6HK1E5S
Type	OHC, Direct Injection, Turbo Charged with intercooler, EGR, Watercooled, 6 cylinders, Common Rail System
Displacement (cc)	7,790
Max. Output	300 ps / 2,400 rpm
Max. Torque	100kg-m / 1,400 ~2,400rpm
<b>Transmission</b>	
Type	MAL7Q 7-speed overdrive
Gear ratio	1st ~ 7th: 6.307 ~ 0.677
Final Gear ratio	5.571
<b>Clutch</b>	
Type	Dry single plate w/cushioning spring,
<b>Steering</b>	
Type	Recirculating ball, power assisted
<b>Suspension</b>	
Front & Rear	Air suspension with stabilizer
<b>Brake</b>	
Service	Full air, Dual Circuit, ABS and air dryer, Brake auto adjuster
Parking	Spring brake actuators acting on rear wheels
Auxiliary	Permanent magnetic retarder, Exhaust Brake
<b>Tire &amp; Disc</b>	
Disc Wheel	22.5 X 8.25 (10 studs)
Tire	12R22.5 Radial Tubeless
<b>Standard Equipment</b>	
	Clutch minipack control, Exhaust brake, Air dryer with heavy duty air compressor, Anti Lock brake system, Tachometer, Abestos free brake & clutch linings

<b>型號</b>	<b>LV434V</b>
<b>規格</b>	
<b>車陣尺寸</b>	
全長(毫米)	8,654
全闊(毫米)	2,447
軸距(毫米)	3,000
總重量 (公斤)	16,000
<b>引擎</b>	
型號	6HK1E5NC
類別	頂置凸輪軸，直接噴注，渦輪增壓附中置冷卻器，廢氣再循環裝置，水冷式，6 氣缸，電子控制高壓共軌噴注系統
汽缸容積 (cc)	7,790
最大輸出	300 ps / 2,400 rpm
最大扭力	100kg-m / 1,400 ~2,400rpm
<b>波箱</b>	
型號	MAL7Q 76前速超速檔
波段比	1波 ~ 7波: 6.307 ~ 0.677
最終傳動比	5.571
<b>離合器</b>	
類別	單乾板式附緩衝彈簧，液壓控制
<b>轉向系統</b>	
類別	迴旋走珠式，動力輔助
<b>懸掛系統</b>	
類別	氣壓懸掛附吸震筒
<b>制動系統</b>	
制動操作	全風雙迴路，防鎖剎車系統 (ABS)，自動攝迫力皮
泊車手制	後輪彈簧制動器
輔助制動系統	恆久式磁力輔助制動器，廢氣制動
<b>車胎</b>	
車輪	22.5 X 8.25 (10螺絲)
輪胎	11R22.5無內膽原子胎
<b>標準裝備</b>	
	動力輔助離合器，廢氣制動，空氣乾燥器連特強空氣壓縮器，防鎖剎車系統 (ABS)，引擎轉數錶，無石棉環保迫力皮及離合器片

042014

- 以上規格如有更改，恕不另行通告。  
- 圖示之設備可能與實物稍異。  
- 備有耗油量資料可供查閱。  
此引擎符合廢氣管制環保5(Euro5)  
及香港噪音管制標準。