

全新五十鈴環保6型D-MAX PICKUP 多用途車							
Model	TFR87JS-VI	TFS87JE-VI	TFS87JE-VI-AT	TFR87JD-VI	TFS87JD-VI	TFS87JD-VI-AT	TFS87JD-VI-AT-D
Emission Standard	環保六型						
Driving System	4 x 2	4 x 4	4 x 4	4 x 2	4 x 4	4 x 4	4 x 4
G.V.W. (kg)	3,000	3,050	3,050	3,000	3,000	3,000	3,000
Seating Capacity	2	4	4	2	5	5	5
Dimensions							
Overall Length (mm)	5,315	5,295	5,295	5,295	5,295	5,295	5,295
Overall Width (mm)	1,775	1,860	1,860	1,860	1,860	1,860	1,860
Overall Height (mm)	1,685	1,790	1,790	1,785	1,785	1,795	1,795
Wheelbase (mm)	3,095	3,095	3,095	3,095	3,095	3,095	3,095
Engine							
Model	RZ4EE6S-L						
Type	In-line, 4 cylinders, DOHC, Variable Geometry System Turbocharger (VGS Turbo) with Intercooler Exhaust Gas Recirculation (EGR), Common Rail System (CRS), Lean NOx Trap (LNT) +Diesel Particulate Diffuser (DPD)						
Displacement (cc)	1,898						
Max. Output (PS/rpm)	163 / 3,600						
Max. Torque (kgm/rpm)	36.7 / 2,000~2,500						
Fuel Tank Capacity (litre)	76						
Transmission							
Model	MVL-6N 6 Forward 1 Reverse, Manual Transmission	MVL-6N 6 Forward 1 Reverse, Manual Transmission	AWE6B45-II 6 Forward 1 Reverse, Automatic Transmission	MVL-6N 6 Forward 1 Reverse, Manual Transmission	MVL-6N 6 Forward 1 Reverse, Manual Transmission	AWE6B45-II 6 Forward 1 Reverse, Automatic Transmission	AWE6B45-II 6 Forward 1 Reverse, Automatic Transmission
Gear Ratios	1~6 Gear : 4.942~ 0.634	1~6 Gear : 4.942~ 0.634	1~6 Gear : 3.6~ 0.580	1~6 Gear : 4.942~ 0.634	1~6 Gear : 4.942~ 0.634	1~6 Gear : 3.6~ 0.580	1~6 Gear : 3.6~ 0.580
Final Gear Ratio	3.909	4.3	4.3	4.3	4.3	4.3	4.3
Clutch							
Type	Hydraulic controlled, dry single plate	Hydraulic controlled, dry single plate	N/A	Hydraulic controlled, dry single plate	Hydraulic controlled, dry single plate	N/A	N/A
Steering							
Type	Power assisted, rack & pinion type						
Suspension							
Front	Independent wishbone, coil spring, Double wishbone suspension with torsion bar						
Rear	Semi-elliptical alloy steel leaf spring, Banjo, semi-floating type						
Brake							
Servioe	Front disc, Rear drum, Vacuum servo hydraulic						
Parking	Mechanical parking brake						
Auxiliary	Anti-lock Brake System (ABS) with Electronic Braking Force Distribution (EBD), Brake Assist (BA), Electronic Stability Control (ESC), Hill-Start-Aid (HSA), Hill Descent Control (HDC)						
Frame							
Type	Box cross section type						
Width (mm)	1,120						
Tire&Wheel							
Tire	215/70R15C	255/60R18	255/60R18	215/70R15C	245/70R16	255/60R18	255/60R18
Wheel	15 x 6.5 (6 studs)	18 x 7.0 (6 studs) Aluminium Wheel	18 x 7.0 (6 studs) Aluminium Wheel	15 x 6.5 (6 studs)	16 x 7.0 (6 studs)	18 x 7.0 (6 studs) Aluminium Wheel	18 x 7.0 (6 studs) Aluminium Wheel

全新五十鈴環保6型D-MAX PICKUP 多用途車							
型號	TFR87JS-VI	TFS87JE-VI	TFS87JE-VI-AT	TFR87JD-VI	TFS87JD-VI	TFS87JD-VI-AT	TFS87JD-VI-AT-D
廢氣排放標準	環保六型						
驅動系統	4 x 2	4 x 4	4 x 4	4 x 2	4 x 4	4 x 4	4 x 4
總重量(公斤)	3,000	3,050	3,050	3,000	3,000	3,000	3,000
乘客量(連司機)	2	4	4	2	5	5	5
車身尺寸							
全長(毫米)	5,315	5,295	5,295	5,295	5,295	5,295	5,295
全闊(毫米)	1,775	1,860	1,860	1,860	1,860	1,860	1,860
全高(毫米)	1,685	1,790	1,790	1,785	1,785	1,795	1,795
軸距(毫米)	3,095	3,095	3,095	3,095	3,095	3,095	3,095
引擎							
型號	RZ4EE6S-L						
類別	直列四汽缸，雙頂凸輪軸，可變活瓣渦輪增壓 (VGS Turbo)連中置冷卻器，廢氣再循環裝置 (EGR)，電子控制高壓共軌噴注系統 (CRS)，稀油氣氧化物捕集器+柴油微粒過濾器(LNT+DPF)						
汽缸容積(毫升)	1,898						
最大馬力(匹/轉)	163 / 3,600						
最大扭矩(公斤-米/轉)	36.7 / 2,000~2,500						
油缸容積(公升)	76						
波箱							
型號	MVL-6N 6前1後手動波箱	MVL-6N 6前1後手動波箱	AWE6B45-II 6前1後全自動波箱	MVL-6N 6前1後手動波箱	MVL-6N 6前1後手動波箱	AWE6B45-II 6前1後全自動波箱	AWE6B45-II 6前1後全自動波箱
波段比	1~6波 : 4.942~ 0.634	1~6波 : 4.942~ 0.634	1~6波 : 3.6~ 0.580	1~6波 : 4.942~ 0.634	1~6波 : 4.942~ 0.634	1~6波 : 3.6~ 0.580	1~6波 : 3.6~ 0.580
最終傳動比	3.909	4.3	4.3	4.3	4.3	4.3	4.3
離合器							
類別	液壓控制，單乾板 式	液壓控制，單乾板 式	不適用	液壓控制，單乾板 式	液壓控制，單乾板 式	不適用	不適用
轉向系統							
懸掛系統	動力輔助齒條齒輪式						
前懸掛	獨立搖臂配圓形彈簧，雙橫臂式懸架連扭力桿						
後懸掛	半橢圓形合金鋼片彈簧，琵琶型半浮式						
制動系統							
制動操作	前碟、後鼓、真空液壓式						
停車手制	機械式手掣						
輔助制動	防鎖死制車系統 (ABS)連電子制動力分佈系統 (EBD)，輔助制動系統 (BA)，電子車禍穩定控制系統 (ESC)，斜坡起動輔助系統 (HSA)，下坡輔助控制 (HDC)						
車陣							
類型	盒式切面車陣						
陣闊(毫米)	1,120						
輪胎及車輪							
車胎	215/70R15C	255/60R18	255/60R18	215/70R15C	245/70R16	255/60R18	255/60R18
車輪	15 x 6.5 (6 螺絲)	18 x 7.0 (6 螺絲) 鋁合金輪圈	18 x 7.0 (6 螺絲) 鋁合金輪圈	15 x 6.5 (6 螺絲)	16 x 7.0 (6 螺絲)	18 x 7.0 (6 螺絲) 鋁合金輪圈	18 x 7.0 (6 螺絲) 鋁合金輪圈