

全新五十鈴環保6型D-MAX PICKUP 多用途車

Model	TFR87JS-VI	TFS87JE-VI	TFS87JE-VI-AT	TFR87JD-VI	TFS87JD-VI	TFS87JD-VI-AT	TFS87JD-VI-AT-D
Emission Standard	環保六型						
Driving System	4 x 2	4 x 4	4 x 4	4 x 2	4 x 4	4 x 4	4 x 4
G.V.W. (kg)	3,000	3,050	3,050	3,000	3,000	3,000	3,000
Seating Capacity	2	4	4	5	5	5	5
Dimensions							
Overall Length (mm)	5,315	5,295	5,295	5,295	5,295	5,295	5,295
Overall Width (mm)	1,775	1,860	1,860	1,775	1,860	1,860	1,860
Overall Height (mm)	1,685	1,790	1,790	1,690	1,785	1,795	1,795
Wheelbase (mm)	3,095	3,095	3,095	3,095	3,095	3,095	3,095
Engine							
Model	RZ4EE6S-L						
Type	In-line, 4 cylinders, DOHC, Variable Geometry System Turbocharger (VGS Turbo) with Intercooler Exhaust Gas Recirculation (EGR), Common Rail System (CRS), Lean NOx Trap (LNT) +Diesel Particulate Diffuser (DPD)						
Displacement (cc)	1,898						
Max. Output (PS/rpm)	163 / 3,600						
Max. Torque (kgm/rpm)	36.7 / 2,000~2,500						
Fuel Tank Capacity (litre)	76						
Transmission							
Model	MVL-6N 6 Forward 1 Reverse, Manual Transmission	MVL-6N 6 Forward 1 Reverse, Manual Transmission	AWR6B45-II 6 Forward 1 Reverse, Automatic Transmission	MVL-6N 6 Forward 1 Reverse, Manual Transmission	MVL-6N 6 Forward 1 Reverse, Manual Transmission	AWR6B45-II 6 Forward 1 Reverse, Automatic Transmission	AWR6B45-II 6 Forward 1 Reverse, Automatic Transmission
Gear Ratios	1 ~ 6 Gear : 4.942 ~ 0.634	1 ~ 6 Gear : 4.942 ~ 0.634	1 ~ 6 Gear : 3.6 ~ 0.580	1 ~ 6 Gear : 4.942 ~ 0.634	1 ~ 6 Gear : 4.942 ~ 0.634	1 ~ 6 Gear : 3.6 ~ 0.580	1 ~ 6 Gear : 3.6 ~ 0.580
Final Gear Ratio	3.909	4.3	4.3	3.909	4.3	4.3	4.3
Clutch							
Type	Hydraulic controlled, dry single plate	Hydraulic controlled, dry single plate	N/A	Hydraulic controlled, dry single plate	Hydraulic controlled, dry single plate	N/A	N/A
Steering							
Type	Power assisted, rack & pinion type						
Suspension							
Front	Independent wishbone, coil spring, Double wishbone suspension with torsion bar						
Rear	Semi-elliptical alloy steel leaf spring, Banjo, semi-floating type						
Brake							
Servioe	Front disc, Rear drum, Vacuum servo hydraulic						
Parking	Mechanical parking brake						
Auxiliary	Anti-lock Brake System (ABS) with Electronic Braking Force Distribution (EBD), Brake Assist (BA), Electronic Stability Control (ESC), Hill-Start-Aid (HSA), Hill Descent Control (HDC)						
Frame							
Type	Box cross section type						
Width (mm)	1,120						
Tire&Wheel							
Tire	215/70R15C	255/60R18	255/60R18	215/70R15C	245/70R16	255/60R18	255/60R18
Wheel	15 x 6.5 (6 studs)	18 x 7.0 (6 studs) Aluminium Wheel	18 x 7.0 (6 studs) Aluminium Wheel	15 x 6.5 (6 studs)	16 x 7.0 (6 studs)	18 x 7.0 (6 studs) Aluminium Wheel	18 x 7.0 (6 studs) Aluminium Wheel