

全新五十鈴環保6型30噸車陣

	CYH52手液型號	
型號 Model	CYH52SD-7S-VI-C	CYH52TX-7S-VI-C
廢氣排放標準 Emission Standard	環保六型 Euro VI	
總重量(公斤) G.V.W. (kg)	30,000	
乘客量(連司機) Seating Capacity	1 + 2 座位	
車身尺寸 Dimensions		
全長(毫米) Overall Length (mm)	8,840	10,665
全闊(毫米) Overall Width (mm)	2,490	2,490
全高(毫米) Overall Height (mm)	3,015	2,985
輪距(毫米) Wheelbase (mm)	5,650	5,980
引擎 Engine		
型號 Model	6WG1E6N	
類別 Type	直列式六氣缸，24氣閥，可變活瓣渦輪增壓 (VGS Turbo)連中置冷卻器， 廢氣再循環裝置 (EGR)，電子控制高壓共軌噴注系統 (CRS) 柴油微粒過濾器+選擇性催化還原 (DPD+SCR) In-line, 6 Cylinders, 24 Valves, Variable Geometry System Turbocharger (VGS Turbo) with Intercooler Exhaust Gas Recirculation (EGR), Common Rail System (CRS), Diesel Particulate Diffuser (DPD) + Selective Catalytic Reduction (SCR)	
汽缸容積(毫升) Displacement (cc)	15,681	
最大馬力(匹/轉) Max. Output (PS/rpm)	420 / 1,800	
最大扭力(公斤·米/轉) Max. Torque (kgm/rpm)	190 / 1,300	
油缸容積(公升) Fuel Tank Capacity (litre)	300	400
尿素缸容積(公升) Adblue Tank Capacity (litre)	28	
波箱 Transmission		
型號 Model	MJT7S 7前1後 手動波箱 7 Forward 1 Reverse, Manual	
波段比 Gear Ratios	1 ~ 7波: 6.833 ~ 0.728	
最終傳動比 Final Gear Ratio	5.125	4.875
離合器 Clutch		
類別 Type	單乾板式附避震彈簧，空氣輔助液壓控制 Dry Single Plate with Cushioning Spring, Hydraulic Control with Air Assisted	
轉向系統 Steering		
類型 Type	走珠式動力輔助轉向系統 Recirculating Ball with Power Assisted	
懸掛系統 Suspension		
前懸掛 Front	半橢圓鋼合金多層葉片式彈簧，雙重液壓吸震筒 Semi-elliptical, Alloy Steel Leaf Spring, Double Acting Telescopic Shock Absorber	龍船葉片式彈簧，雙重液壓吸震筒 Taper Leaf Spring, Double Acting Telescopic Shock Absorber
後懸掛 Rear	半橢圓鋼合金多層葉片式彈簧 Semi-elliptical, Alloy Steel Leaf Spring	龍船葉片式彈簧 Taper Leaf Spring
前軸 Front Axle	倒置愛里奧工字架 Reverse Elliot "I" Beam	
廠方設計負重(公斤) Design Axle Loading (kg)	7,500 + 7,500	
運輸署批核負重(公斤) Allocated Weight (kg)	7,100 + 7,100	
後軸 Rear Axle	琵琶全浮內擺線齒輪 Banjo, Full Floating Type, Hypoid Gear	
廠方設計負重(公斤) Design Axle Loading (kg)	10,500 + 10,500	
運輸署批核負重(公斤) Allocated Weight (kg)	9,000 + 9,000	
制動系統 Brake		
制動操作 Service	前後鼓刹，全風雙管路楔式制動，虛位自動調節器，ABS防鎖剎車系統 Front&Rear Drum, Full Air, Dual Circuit, Wedge Type, Brake Auto Adjuster, Anti-lock Brake System (ABS)	
停車手制 Parking	後輪彈簧制動器 Spring Brake Actuators Acting on Rear Wheels	
輔助制動 Auxiliary	廢氣剎車，斜坡起動輔助系統(HSA) Exhaust Brake, Hill-Start-Aid (HSA)	
車陣 Frame		
類型 Type	梯型車陣 Ladder Type	
陣闊(毫米) Width (mm)	850	
輪胎及車輪 Tire&Wheel		
車胎 Tire	295/80R22.5 無內膽原子胎	295/80R22.5 Tubeless Radial Tire
車輪 Wheel	22.5 x 8.25 (10 螺絲)	22.5 x 8.25 (10 Stud)
標準裝備 Standard Equipment		
	原廠冷氣，電腦錶板多功能顯示器(MID) AM/FM收音連CD機，駕駛席SRS安全氣囊 電動揭屋仔，氣墊避震駕駛室，氣墊座椅(駕駛座) 電動車窗，車門轉向輔助燈，中央門鎖 電動摺鏡臂(乘客座)，發熱線倒後鏡 Factory Built Air Conditioner, Multi-Information Display (MID) AM/FM CD Player, SRS Airbag on Driver Side Electrical Driven Tilt Cab, Cushioning Cab, Air Suspension Driver's Seat, Power Windows, Door Mount Cornering Lamps, Central Door Lock Electronic Retractable Side Mirror (Passenger Side), Heated Side Mirrors	